DirectTex®
Backlite Premium

Fields of application

.02 .04 .05 .07

Specifications

REF. 599280 139

100 % polyester
knit fabrics
PVC-free, recyclable

ca. 252/ 505 cm
ca. 99/ 199 inch
other widths available on request

B-s1, d0 DIN EN 13501-1
Class A ASTM E48-16
NFPA 701 California Title 19

ca. 260 g/m²
ca. 7.7 oz/yd²

ca. 0.5 mm
ca. 500 µm

rolls
50 m
55 yd

Light
blank: 15.1 %
DIN EN 410

blank: 6
DIN EN ISO 105-B02

indirect light

cold, ultrasonic cut

Printing methods

print	UV	Latex	Dyesub
Inside	•		•
Outside			

Article shrinkage
(50 sec hold up time)

	shrinkage in cross direction	shrinkage in longitudinal direction	recommended fixing temperature
180°C	0,4 %	0,7 %	•
190°C	0,6 %	1,2 %	
200°C	0,8 %	1,4 %	
210°C	1,3 %	2,0 %	

Certifications

OEKO-TEX® CONFIDENCE IN TEXTILES STANDARD 100 09.0.67573 HOHENSTEIN HTTI Tested for harmful substances. www.oeko-tex.com/standard100

PONGS GROUP GMBH & CO. KG
Bahnhofstraße 21
07919 Pausa-Mühltroff
Germany
Phone +49 36645 350-0
salestt@pongs.com
www.pongs.com

Find the latest version by scanning the QR code.
We reserve the right for technical modifications.
The above mentioned details are non-binding.
A tolerance of ± 5% is valid. Effective: 2021/12

DirectTex®
Backlite Premium

Fields of application

.02 .04 .05 .07

Ref.-Nr.: 599280 139 | Preview print sample

PONGS GROUP GMBH & CO. KG
Bahnhofstraße 21
07919 Pausa-Mühltroff
Germany

Phone +49 36645 350-0
salestt@pongs.de
www.pongs.com

Find the latest version by scanning the QR code.
We reserve the right for technical modifications.
The above mentioned details are non-binding.
A tolerance of ± 5% is valid. Effective: 2021/12