

## Technical Data Sheet

[www.soletex.com](http://www.soletex.com)

<b>Article- No</b>	KW 012 - RASCHEL (Matt Flag)	
<b>Application</b>	Flag / Beach Flag	
<b>Printable Ink</b>	Treatment applied for Sub Paper , Direct Sub.	
<b>Material</b>	100 % Polyester	
<b>Standart Sizes</b>	270 cm,320 cm (106",126") x 100mt.(109 yrd.)	
<b>Weight</b>	110 ( g/m2 )+- 5(gr) (3,8 oz)	
<b>Tensile Strength</b>	38/84 warp/weft (daN)	DIN EN ISO 13934-1
<b>Tear Resistance</b>	37/45 warp/weft (N)	DIN EN ISO 13937-4
<b>Finishing</b>	Digital Coating	

**Packaging** 3" paper core, wrapped with stretch film + put in a cardboard box or tubes

Our product enables to have vivid colors and good printing quality with SUBLIMATION inks.  
(Test printing is suggested before the printing job.)



Ink Type

**SUB**

Sub Direct and Paper Transfer

\*Optional



Fire Retardant

**B1**

Fire Retardant

**M1**

Fire Retardant

**EN 13501**

Fire Retardant

**NFPA 701**

Fire Retardant



Cutting

**COLD**

Cold Cut

All above released specifications and informations are for guidance purposes only. Our policy of continuous improvement may result in changes , we therefore reserve the right to alter the specifications and the informations at anytime without notice.