

## LAMINATION

|          |           |                    |
|----------|-----------|--------------------|
| PVC Film | Type      | Monomeric PVC Film |
|          | Color     | Transparent        |
|          | Finishing | Matte              |
|          | Weight    | 85 gsm             |
|          | Thickness | 65±5 Micron        |

|          |                    |                               |
|----------|--------------------|-------------------------------|
| Adhesive | Type               | Clear Solvent Press Sensitive |
|          | Peeling Force      | ≥ 6N/25mm                     |
|          | Holding Power      | ≥ 1000 minutes                |
|          | Gluing Temperature | 10-45°C                       |
|          | Thickness          | 18 Micron                     |

|               |        |                             |
|---------------|--------|-----------------------------|
| Release Paper | Type   | Single Side PE Coated Paper |
|               | Color  | White                       |
|               | Weight | 95 ± 5 gsm                  |

|                       |   |
|-----------------------|---|
| Operating Temperature | 15-35°C   |
| Shelf Life            | 1 Year (Storage temperature 20-30°C, relative humidity of 45-55%) |
| Applications          | It is designed for outdoor and indoor Decoration, Advertising etc |
| Width                 | 0.914m, 1.27m, 1.37m, 1.52m                                       |
| Length                | 50m   |

\* Our product enables us to have vivid colors and good printing quality. (Test printing is suggested before the printing job.)



All above-released specifications and information are for guidance purposes only. Our policy of continuous improvement may result in changes. We therefore reserve the right to alter the specifications and the information at any time without notice.