

DirectTex[®]

Softimage Creaseless Premium[®]

Fields of application

.02 .04 .05 .07

Specifications



599221 159



100 % polyester
knit fabrics
PVC-free, recyclable



ca. 160/ 252/ 320/ 505 cm
ca. 63/ 99/ 126/ 199 inch
other widths available on request



B-s1, d0 DIN EN 13501-1
M1 NF P 92 503-507
NFFPA 701



ca. 220 g/m²
ca. 6.5 oz/yd²



ca. 0.41 mm
ca. 410 μm



rolls
50/ 100 m
55/ 109 yd



length: 438.7 N
cross: 1477.4 N
DIN EN ISO 13934-1



length: 50.7 %
cross: 50.6 %
DIN EN ISO 13934-1



blank: 7
DIN EN ISO 105-B02



length: 1.5 %
cross: 0.5 %
DIN EN 14704-1



cold, ultrasonic cut

Printing methods

print	UV	Latex	Dyesub
Inside	•	•	•
Outside			•

Article shrinkage (50 sec hold up time)

	shrinkage in cross direction	shrinkage in longitudinal direction	recommended fixing temperature
180°C	1,5 %	0,8 %	
190°C	1,7 %	0,9 %	•
200°C	2,2 %	1,0 %	
210°C	3,5 %	1,2 %	

Certifications



DirectTex® Softimage Creaseless Premium®

Fields of application

.02 .04 .05 .07



Ref.-Nr.: 599221 159 | Preview print sample