

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No. 453/2010 - United Kingdom (UK)

SAFETY DATA SHEET

BSK FLEX Magenta

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product no. : 1506859

Product name : BSK FLEX Magenta

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses: Printing inks, coatings, toners, and related materials

Uses advised against: Not Available

1.3 Details of the supplier of the safety data sheet

INX International Ink Co. 150 N Martingale Rd, Suite 700 Schaumburg

Illinois 60173

United States

e-mail address of person : MSDS@inxintl.com

responsible for this SDS

1.4 Emergency telephone number

24 Hour Emergency Phone : 800.535.5053 INFOTRAC 24 Hour Spill and Emergency (+1 352

323 3500 outside of North America)

National advisory body/Poison Center

Telephone number: Not available.Hours of operation: Not available.Information limitations: Not available.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Skin Corr./Irrit. 2, H315 Eye Dam./Irrit. 2, H319 Skin Sens. 1, H317

Repr. 2, H361f (Fertility) Repr. 2, H361d (Unborn child)

STOT RE 2, H373 Aquatic Chronic 2, H411

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

2.2 Label elements

Hazard pictograms





Signal word

Hazard statements Causes serious eye irritation.

Causes skin irritation.

May cause an allergic skin reaction.

Suspected of damaging fertility. Suspected of damaging the unborn

May cause damage to organs through prolonged or repeated

exposure.

Toxic to aquatic life with long lasting effects.

Precautionary statements

General Read label before use.

Prevention Obtain special instructions before use. Wear protective gloves. Wear

eye or face protection. Avoid release to the environment. Do not

breathe vapor.

Get medical attention if you feel unwell. IF exposed or concerned: Response

Get medical attention.

Storage

Disposal Dispose of contents and container in accordance with all local,

regional, national and international regulations.

Hazardous ingredients 2-phenoxyethyl acrylate

exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate

1-vinylhexahydro-2H-azepin-2-one

diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide

Supplemental label elements Not applicable.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures

Not applicable.

and articles

Special packaging requirements

Containers to be fitted with child-resistant fastenings

Not applicable.

Tactile warning of danger Yes, applicable.

2.3 Other hazards

Substance meets the criteria for Not applicable.

PBT according to Regulation (EC) No. 1907/2006, Annex XIII

Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

Not applicable.

Other hazards which do not result in classification

None known.

SECTION 3: Composition/information on ingredients

3.1 Substances : Not applicable

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification Regulation (EC) No. 1272/2008 [CLP]	Туре
2-phenoxyethyl acrylate	EC:256-360-6 Index:	>=35 - <50	Skin Sens. 1, H317 Aquatic Chronic 2, H411	[1]
exo-1,7,7- trimethylbicyclo[2.2.1]hept- 2-yl acrylate	EC:227-561-6 Index:	>=15 - <20	Skin Corr./Irrit. 2, H315 Eye Dam./Irrit. 2, H319 Skin Sens. 1, H317 STOT SE 3, H335 Aquatic Chronic 2, H411	[1]
Amine Modified Acrylate Oligomer	EC:	>=7 - <10	Skin Corr./Irrit. 2, H315 Eye Dam./Irrit. 2, H319	[1]
1-vinylhexahydro-2H- azepin-2-one	EC:218-787-6 CAS: 2235-00-9 Index:	>=7 - <10	Acute Tox. 4, H302 (oral) Acute Tox. 4, H312 (dermal) Eye Dam./Irrit. 2, H319 Skin Sens. 1, H317 STOT RE 1, H372 (liver, respiratory tract)	[1]
diphenyl(2,4,6- trimethylbenzoyl)phosphine oxide	EC:278-355-8	>=5 - <7	Repr. 2, H361f (Fertility) Repr. 2, H361d (Unborn child) Aquatic Chronic 3, H412	[1]
Neopentyl Propoxylate Diacrylate	EC:617-546-6 Index:	>=3 - <5	Skin Sens. 1, H317 Aquatic Chronic 2, H411	[1]
hexamethylene diacrylate	EC:235-921-9 Index:607-109- 00-8	>=3 - <5	Skin Corr./Irrit. 2, H315 Eye Dam./Irrit. 2, H319 Skin Sens. 1, H317	[1][2]
2-phenoxyethanol	EC:204-589-7	>=1 - <2	Acute Tox. 4, H302 (oral) Eye Dam./Irrit. 2, H319	[1]

CAS: 122-99-6		
Index:603-098-		
00-9		

Type

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
- [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII
- [5] Substance of equivalent concern

See Section 16 for the full text of the R phrases or H statements declared above.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses.

Continue to rinse for at least 10 minutes. Get medical attention.

Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person

may need to be kept under medical surveillance for 48 hours. Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

Inhalation

Skin contact

Ingestion

Protection of first-aiders

4.2 Most important symptoms and effects, both acute and delayed

Date of previous issue: 04.11.2015 Version: 1.4 Date of issue/Date of revision: 27.01.2016

BSK FLEX Magenta Page: 5/17

Potential acute health effects

Eye contact Causes serious eye irritation.

Inhalation Exposure to decomposition products may cause a health hazard.

Serious effects may be delayed following exposure.

Skin contact Causes skin irritation. May cause an allergic skin reaction.

Ingestion Irritating to mouth, throat and stomach.

Over-exposure signs/symptoms

Eye contact Adverse symptoms may include the following:

pain or irritation

watering redness

Inhalation Adverse symptoms may include the following:

> reduced fetal weight increase in fetal deaths skeletal malformations

Skin contact Adverse symptoms may include the following:

> irritation redness

reduced fetal weight increase in fetal deaths skeletal malformations

Ingestion Adverse symptoms may include the following:

> reduced fetal weight increase in fetal deaths skeletal malformations

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician In case of inhalation of decomposition products in a fire, symptoms

may be delayed. The exposed person may need to be kept under

medical surveillance for 48 hours.

No specific treatment. **Specific treatments**

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media Use an extinguishing agent suitable for the surrounding fire. Unsuitable extinguishing media None known.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture

In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or

Date of issue/Date of revision: 27.01.2016 Version: 1.4 Date of previous issue: 04.11.2015 Hazardous thermal decomposition products

drain.

 Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides

sulfur oxides phosphorus oxides

5.3 Advice for firefighters

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

: Not available.

Additional information

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders

If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

6.3 Methods and materials for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the

same hazard as the spilled product.

6.4 Reference to other sections

: See Section 1 for emergency contact information.

See Section 8 for information on appropriate personal protective equipment.

See Section 13 for additional waste treatment information.

Page: 7/17

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures

Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. . Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Seveso II Directive - Reporting thresholds

Danger criteria

Category	Notification and MAPP threshold	Safety report threshold
E2: Hazardous to the aquatic environment - Chronic 2	200 kg	500 kg

7.3 Specific end use(s)

Recommendations : Not available. **Industrial sector specific** : Not available.

solutions

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker or exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
hexamethylene diacrylate	AIHA WEEL (1999-01-01) Notes: AIHA dermal sensitization
	Time Weighted Average (TWA) 1 mg/m3
	MAK-Werte Liste (2002-07-01) Notes: Danger of sensitization of the
	skin See Section IV: Sensitizing substances

Recommended monitoring procedures

If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNEL/DMEL Summary

Not available.

PNEC Summary

Not available.

8.2 Exposure controls

Appropriate engineering controls

If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Page:9/17

Eye/face protection

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Skin protection

Hand protection

chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state: liquidColor: Red.

Odor:Not available.Odor threshold:Not available.pH:Not available.Melting point/freezing point:Not available.Initial boiling point and boiling:Not available.

range

Flash point : Not Measured. Material is not expected to flash.

Evaporation rate : Not available.

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No. 453/2010 BSK FLEX Magenta Page: 10/17

Flammability (solid, gas) : Not available.

Upper/lower flammability or : **Lower:** Not available. **explosive limits** Upper: Not available.

Vapor pressure : Not available.
Vapor density : Not available.

Relative density : 1,02

Solubility(ies) : Not available.

Partition coefficient: n- : Not available.

octanol/water

Auto-ignition temperature : Not available. **Decomposition temperature** : Not available.

Viscosity : Dynamic: Not available.

Kinematic: Not available.

Explosive properties : Not available. **Oxidizing properties** : Not available.

9.2 Other information

Volatile. : 4,64 %(m) Weight %

4,57 %(V) Volume %

VOC % : 1,79 %(m) Weight %

1,65 %(V) Volume %

Coating VOC : 0,16 lb/gal

19 g/l

SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or

its ingredients.

10.2 Chemical stability : The product is stable.

10.3 Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions

will not occur.

10.4 Conditions to avoid : No specific data.

10.5 Incompatible materials : No specific data.

10.6 Hazardous decomposition :

products

: Under normal conditions of storage and use, hazardous

decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure		
Monofunctional Monomer						
Multi-functional Monomer						
	LD50 Oral	Rat	4.890 mg/kg	-		
Amine Modified Acrylate Ol	Amine Modified Acrylate Oligomer					

1-Vinylhexahydro-2H-azepin	n-2-one			
Photoinitiator				
	LD50 Oral	Rat	5.000 mg/kg	-
Diacrylate Oligomer				
Diacrylate Monomer				
	LD50 Oral	Rat	5.000 mg/kg	-
Ethanol, 2-phenoxy-				
	LD50 Oral	Rat	1.260 mg/kg	-
	LD50 Dermal	Rat	14.422 mg/kg	-

Conclusion/Summary : Not available.

Acute toxicity estimates

Not available.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
2-phenoxyethanol	Eyes -	Rabbit	-	24 hrs	-
	Severe				
	irritant				
2-phenoxyethanol	Skin - Mild	Rabbit	-	24 hrs	-
	irritant				
2-phenoxyethanol	Eyes -	Rabbit	-		-
	Moderate				
	irritant				

Conclusion/Summary

Skin:Not available.Eyes:Not available.Respiratory:Not available.

Sensitization

Conclusion/Summary

Skin: Not available.Respiratory: Not available.

Mutagenicity

Conclusion/Summary : Not available.

Carcinogenicity

Conclusion/Summary : Not available.

Reproductive toxicity

Conclusion/Summary : Not available.

Teratogenicity

Conclusion/Summary : Not available.

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs

exo-1,7,7-	Category 3	Respiratory tract irritation
trimethylbicyclo[2.2.1]hept-2-yl		
acrylate		

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
1-vinylhexahydro-2H-azepin-2-			
one			

Aspiration hazard

Not available.

Information on the likely routes

of exposure

Not available.

Potential acute health effects

Eye contact : Causes serious eye irritation.

Inhalation : Exposure to decomposition products may cause a health hazard.

Serious effects may be delayed following exposure.

Skin contact : Causes skin irritation. May cause an allergic skin reaction.

Ingestion: Irritating to mouth, throat and stomach.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : Adverse symptoms may include the following:

pain or irritation

watering redness

Inhalation : Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

Skin contact : Adverse symptoms may include the following:

irritation redness

reduced fetal weight increase in fetal deaths skeletal malformations

Ingestion : Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects : Not available.
Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.
Potential delayed effects : Not available.

Potential chronic health effects

Conclusion/Summary : Not available.

General: May cause damage to organs through prolonged or repeated

exposure. Once sensitized, a severe allergic reaction may occur

when subsequently exposed to very low levels.

Carcinogenicity: No known significant effects or critical hazards.Mutagenicity: No known significant effects or critical hazards.Teratogenicity: Suspected of damaging the unborn child.Developmental effects: No known significant effects or critical hazards.

Fertility effects : Suspected of damaging fertility.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
2-phenoxyethanol			
	Acute LC50 344.000	Fish - Fathead minnow	96 h
	μg/l Fresh water		

Conclusion/Summary : Not available.

12.2 Persistence and degradability

Conclusion/Summary : Not available.

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
2-phenoxyethanol		0,35	low

12.4 Mobility in soil

Soil/water partition coefficient

(KOC)

Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

PBT : P: Not available.

B: Not available.T: Not available.

vPvB vP: Not available.

vB: Not available.

12.6 Other adverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste

: The classification of the product may meet the criteria for a hazardous waste.

Packaging

Methods of disposal

: The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Special precautions

: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

Regulatory	Proper shipping	UN -	Hazard	Packing group	Additional
information	name	Number	classification		information
ADN	Environmentally	UN3082	9	III	
	Hazardous				
	Substance, Liquid,				
	n.o.s. (Acrylates)				
ADR	Environmentally	UN3082	9	III	
	Hazardous				
	Substance, Liquid,				
	n.o.s. (Acrylates)				
IMDG	Environmentally	UN3082	9	III	
	Hazardous				
	Substance, Liquid,				
	n.o.s. (Acrylates),				
	Marine Pollutant				
IATA	Environmentally	UN3082	9	III	
	Hazardous				
	Substance, Liquid,				
	n.o.s. (Acrylates)				

DOT (U.S.A.)	Not classified.		-	
(Pictograms)				
TDG Class	Not classified.		-	
Mexico Classification	Not classified.		-	

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorization

Annex XIV: None of the components are listed.

Substances of very high concern:

Other EU regulations

Europe inventory Integrated pollution prevention and control list (IPPC) - Air Integrated pollution prevention and control list (IPPC) - Water Not determined.
Not listed

Not listed

Aerosol dispensers : Not applicable.

Seveso II Directive

This product is controlled under the Seveso II Directive.

Danger criteria

Ca	ategory
E2	2: Hazardous to the aquatic environment - Chronic 2

National regulations

References : - Guide de la loi et du règlement sur le transport des marchandises

dangeureuses au Canada. Centre de conformité international Ltée. 1986.

International regulations

Chemical Weapons Convention

on : Not listed

List Schedule I Chemicals Chemical Weapons Convention

: Not listed

List Schedule II Chemicals Chemical Weapons Convention

: Not listed

List Schedule III Chemicals

15.2 Chemical Safety Assessment

: This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

Abbreviations and acronyms : ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation

[Regulation (EC) No. 1272/2008] DNEL = Derived No Effect Level DMEL = Derived Minimal Effect Level

EUH statement = CLP-specific Hazard statement PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration

RRN = REACH Registration Number

vPvB = Very Persistent and Very Bioaccumulative

Key literature references and sources for data

 Guide de la loi et du règlement sur le transport des marchandises dangeureuses au Canada. Centre de conformité international Ltée. 1986.

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Skin Corr./Irrit. 2, H315	Calculation method
Eye Dam./Irrit. 2, H319	Calculation method
Skin Sens. 1, H317	Calculation method
Repr. 2, H361f (Fertility)	Calculation method
Repr. 2, H361d (Unborn child)	Calculation method
STOT RE 2, H373	Calculation method
Aquatic Chronic 2, H411	Calculation method

Full text of abbreviated H statements

H302 (oral)	Harmful if swallowed.
H312 (dermal)	Harmful in contact with skin.
H411	Toxic to aquatic life with long
	lasting effects.
H412	Harmful to aquatic life with long
	lasting effects.
H319	Causes serious eye irritation.
H361fd (Fertility, Unborn	Suspected of damaging fertility.
child)	Suspected of damaging the
	unborn child.
H315	Causes skin irritation.
H317	May cause an allergic skin
	reaction.
H372	Causes damage to organs
	through prolonged or repeated
	exposure.
H373	May cause damage to organs
	through prolonged or repeated
	exposure.
H335	May cause respiratory irritation.

Full text of classifications [CLP/GHS]

Acute Tox. 4, H302	ACUTE TOXICITY (oral) -
	Category 4
Acute Tox. 4, H312	ACUTE TOXICITY (dermal) -
	Category 4
Aquatic Chronic 2, H411	AQUATIC HAZARD (LONG-
_	TERM) - Category 2
Aquatic Chronic 3, H412	AQUATIC HAZARD (LONG-
	TERM) - Category 3

Eye Dam./Irrit. 2, H319	SERIOUS EYE DAMAGE/
	EYE IRRITATION - Category 2
Repr. 2, H361fd (Fertility,	TOXIC TO REPRODUCTION
Unborn child)	(Fertility, Unborn child) -
·	Category 2
Skin Corr./Irrit. 2, H315	SKIN
	CORROSION/IRRITATION -
	Category 2
Skin Sens. 1, H317	SKIN SENSITIZATION -
	Category 1
STOT RE 1, H372	SPECIFIC TARGET ORGAN
	TOXICITY (REPEATED
	EXPOSURE) - Category 1
STOT RE 2, H373	SPECIFIC TARGET ORGAN
	TOXICITY (REPEATED
	EXPOSURE) - Category 2
STOT SE 3, H335	SPECIFIC TARGET ORGAN
	TOXICITY (SINGLE
	EXPOSURE) - Category 3

Date of printing: 08.03.2016Date of issue/ Date of revision: 27.01.2016Date of previous issue: 04.11.2015Version: 1.4

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.