

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No. 453/2010 - United Kingdom (UK)

SAFETY DATA SHEET

SMF Light Cyan

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product no. : 1458355

Product name : SMF Light Cyan

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses: Printing inks, coatings, toners, and related materials

Uses advised against: Not Available

1.3 Details of the supplier of the safety data sheet

INX International Ink Co. 150 N Martingale Rd, Suite 700

Schaumburg Illinois 60173 United States

e-mail address of person : MSDS@inxintl.com

responsible for this SDS

1.4 Emergency telephone number

24 Hour Emergency Phone : 800.535.5053 INFOTRAC 24 Hour Spill and Emergency (+1 352

323 3500 outside of North America)

National advisory body/Poison Center

Telephone number: Not available.Hours of operation: Not available.Information limitations: Not available.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Acute Tox. 4, H332 (inhalation) Eye Dam./Irrit. 2, H319

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

Ingredients of unknown toxicity

Percentage of the mixture consisting of ingredient(s) of unknown toxicity: 6,5 %

Page: 2/15

Ingredients of unknown

ecotoxicity

: Percentage of the mixture consisting of ingredient(s) of unknown hazards to the aquatic environment: 87,1 %

2.2 Label elements

Hazard pictograms

(!)

Signal word

: Warning

Hazard statements : Harmful if inhaled.

Causes serious eye irritation.

Precautionary statements

General : Read label before use.

Prevention: Wear eye or face protection. Use only outdoors or in a well-

ventilated area. Avoid breathing vapor.

Response : IF INHALED: Remove victim to fresh air and keep at rest in a

position comfortable for breathing. Call a POISON CENTER or

physician if you feel unwell.

Storage: Not applicable.Disposal: Not applicable.

Hazardous ingredients : 2-butoxyethyl acetate

cyclohexanone

Supplemental label elements Not applicable.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Not applicable.

Special packaging requirements

Containers to be fitted with child-resistant fastenings

Not applicable.

Tactile warning of danger : Yes, applicable.

2.3 Other hazards

Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII

Not applicable.

Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

Not applicable.

Other hazards which do not : None known. result in classification

SECTION 3: Composition/information on ingredients

3.1 Substances : Not applicable

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification Regulation (EC) No. 1272/2008 [CLP]	Туре
2-butoxyethyl acetate	EC:203-933-3 CAS: 112-07-2 Index:607-038- 00-2	>=50 - <70	Acute Tox. 4, H312 (dermal) Acute Tox. 4, H332 (inhalation)	[1][2]
cyclohexanone	EC:203-631-1 CAS: 108-94-1 Index:606-010- 00-7	>=10 - <12,5	Flam. Liq. 3, H226 Acute Tox. 4, H302 (oral) Acute Tox. 4, H332 (inhalation) Eye Dam./Irrit. 2, H319 Aquatic Chronic 3, H412	[1][2]
?-butyrolactone	EC:202-509-5 CAS:96-48-0 Index:	>=3 - <5	Acute Tox. 4, H302 (oral) Skin Corr./Irrit. 2, H315 Eye Dam./Irrit. 2, H319	[1][2]

Type

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
- [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII
- [5] Substance of equivalent concern

See Section 16 for the full text of the R phrases or H statements declared above.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

Inhalation

Eye contact

: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give

mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash

clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion: Wash out mouth with water. Remove dentures if any. Remove victim

to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie,

belt or waistband.

Protection of first-aiders : No action shall be taken involving any personal risk or without

suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give

mouth-to-mouth resuscitation.

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effects

Skin contact

Eye contact : Causes serious eye irritation.

Inhalation : Harmful if inhaled.

Skin contact : No known significant effects or critical hazards.

Ingestion: Irritating to mouth, throat and stomach.

Over-exposure signs/symptoms

Eye contact : Adverse symptoms may include the following:

pain or irritation

watering redness

Inhalation : No specific data.

Skin contact : No specific data.

Ingestion : No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician : Treat symptomatically. Contact poison treatment specialist

immediately if large quantities have been ingested or inhaled.

Specific treatments : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media Unsuitable extinguishing media

- Use an extinguishing agent suitable for the surrounding fire.
- : None known.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture

mixture
Hazardous thermal
decomposition products

- : In a fire or if heated, a pressure increase will occur and the container may burst.
- : Decomposition products may include the following materials: carbon dioxide carbon monoxide

5.3 Advice for firefighters

Special protective actions for fire-fighters

- : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
- Special protective equipment for fire-fighters
- : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

Additional information

: Not available.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders

: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

6.3 Methods and materials for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste

Large spill

disposal contractor.

: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product.

6.4 Reference to other sections

See Section 1 for emergency contact information.
 See Section 8 for information on appropriate personal protective equipment.
 See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

7.3 Specific end use(s)

Recommendations : Not available. **Industrial sector specific** : Not available. **solutions**

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker or exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
2-butoxyethyl acetate	EU OEL (2000-06-01) Time Weighted Average (TWA) 133 mg/m3, 20
	ppm
	EU OEL (2000-06-01) Short Term Exposure Limit 333 mg/m3, 50
	ppm
	EH40/2005 WELs (2001-12-01) Time Weighted Average (TWA) , 20
	ppm
	EH40/2005 WELs (2001-12-01) Short Term Exposure Limit , 50 ppm
cyclohexanone	EU OEL (2000-06-01) Time Weighted Average (TWA) 40,8 mg/m3,
	10 ppm
	EU OEL (2000-06-01) Short Term Exposure Limit 81,6 mg/m3, 20
	ppm
	EH40/2005 WELs (2003-05-01) Notes: Biological monitoring guidance
	values Short Torres Francoura Limit 20 ppm
	Short Term Exposure Limit , 20 ppm EH40/2005 WELs (2003-05-01) Notes: Biological monitoring guidance
	values
	Time Weighted Average (TWA), 10 ppm
	Time weighted the dage (1 with 1 y 10 ppm
?-butyrolactone	## ######### ### (2003-06-15) Notes: Class 3 - dangerous
	Ceiling 2 mg/m3 Form: vapor and/or gases
	MAK-Werte Liste (2010-07-01) Notes: See Section IIb
	NIOSH REL (2005-09-30)
	Tyoterveyslaitos (2011-12-18) Notes: temporary
	Exposure limit 15 min 70 mg/m3, 250 ppm
	Tyoterveyslaitos (2011-12-18) Notes: temporary
	Exposure limit 8 h 14 mg/m3, 50 ppm
	Arbejdstilsynet (1996-12-01) Notes: This substance is considered as
	organic solvent
	Time Weighted Average (TWA) , 50 ppm

Recommended monitoring procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the

measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNEL/DMEL Summary : Not available.

PNEC Summary : Not available.

8.2 Exposure controls

Appropriate engineering controls : Use only with adequate ventilation. Use process enclosures, local

exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or

statutory limits.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical

products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety

showers are close to the workstation location.

Eye/face protection : Safety eyewear complying with an approved standard should be

used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash

goggles.

Skin protection

Hand protection : Chemical-resistant, impervious gloves complying with an approved

standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the

gloves cannot be accurately estimated.

Body protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be

approved by a specialist before handling this product.

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks

involved and should be approved by a specialist before handling this

product.

Respiratory protection : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is

necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe

working limits of the selected respirator.

Environmental exposure controls : Emissions from ventilation or work process equipment should be

checked to ensure they comply with the requirements of

environmental protection legislation. In some cases, fume scrubbers,

filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state : liquid

Color : Light blue-green.

Odor
Odor threshold
PH
Not available.

range

Flash point : 62,22 °C

Evaporation rate : Not available. **Flammability (solid, gas)** : Not available.

Upper/lower flammability or explosive limits : Lower: Not available. Upper: Not available.

Vapor pressure : Not available.
Vapor density : Not available.

Relative density : 0,96

Solubility(ies) : Not available.

Partition coefficient: n- : Not available.

octanol/water

Auto-ignition temperature : Not available. **Decomposition temperature** : Not available.

Viscosity : Dynamic: Not available.

Kinematic: Not available.

Explosive properties : Not available. **Oxidizing properties** : Not available.

9.2 Other information

Volatile. : 92,81 %(m) Weight %

93,3 %(V) Volume %

VOC % : 92,81 %(m) Weight %

93,3 %(V) Volume %

Coating VOC : 7,4 lb/gal 888 g/l

SECTION 10: Stability and reactivity

10.1 Reactivity• No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : The product is stable.

10.3 Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid

: No specific data.

10.5 Incompatible materials

: No specific data.

10.6 Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Butoxyethyl Acetate				
	LD50 Oral	Rat	2.400 mg/kg	-
	LD50 Dermal	Rabbit	1.500 mg/kg	-
Cyclohexanone				
	LD50 Oral	Rat	1.800 mg/kg	-
	LC50	Rat	8000 ppm	4 h
	Inhalation			
Butanolide, 4-				
	LD50 Oral	Rat	1.540 mg/kg	-
	LD50 Oral	Rat	1.580 mg/kg	-

Conclusion/Summary : Not available.

Acute toxicity estimates

Not available.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
2-butoxyethyl acetate	Skin - Mild	Rabbit	-		-
	irritant				
cyclohexanone	Eyes -	Rabbit	-	24 hrs	-
	Severe				
	irritant				
cyclohexanone	Skin - Mild	Human	-	48 hrs	-
	irritant				
cyclohexanone	Skin - Mild	Rabbit	-		-
	irritant				
cyclohexanone	Eyes -	Rabbit	-		-
	Severe				
	irritant				
?-butyrolactone	Skin - Severe	Rabbit	-		-
	irritant				

Conclusion/Summary

Skin: Not available.Eyes: Not available.

Respiratory : Not available.

Sensitization

Conclusion/Summary

Skin: Not available.Respiratory: Not available.

Mutagenicity

Conclusion/Summary : Not available.

Carcinogenicity

Conclusion/Summary : Not available.

Reproductive toxicity

Conclusion/Summary : Not available.

Teratogenicity

Conclusion/Summary : Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on the likely routes : Not available.

of exposure

Potential acute health effects

Eye contact : Causes serious eye irritation.

Inhalation : Harmful if inhaled.

Skin contact : No known significant effects or critical hazards.

Ingestion: Irritating to mouth, throat and stomach.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : Adverse symptoms may include the following:

pain or irritation watering

redness

Inhalation: No specific data.Skin contact: No specific data.Ingestion: No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects : Not available.
Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available. **Potential delayed effects** : Not available.

Potential chronic health effects

Conclusion/Summary : Not available.

GeneralNo known significant effects or critical hazards.CarcinogenicityNo known significant effects or critical hazards.MutagenicityNo known significant effects or critical hazards.TeratogenicityNo known significant effects or critical hazards.Developmental effectsNo known significant effects or critical hazards.Fertility effectsNo known significant effects or critical hazards.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
cyclohexanone			
	Acute LC50 630.000	Fish - Fathead minnow	96 h
	μg/l Fresh water		
	Acute LC50 732.000	Fish - Fathead minnow	96 h
	μg/l Fresh water		
	Acute LC50 527.000	Fish - Fathead minnow	96 h
	μg/l Fresh water		
	Acute EC50 32,9 mg/l	Aquatic plants - Green	72 h
	Fresh water	algae	

Conclusion/Summary : Not available.

12.2 Persistence and degradability

Conclusion/Summary : Not available.

12.3 Bioaccumulative potential

12.4 Mobility in soil

Soil/water partition coefficient : Not available.

(KOC)

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

PBT : P: Not available.

B: Not available. T: Not available.

vPvB : vP: Not available. vB: Not available.

12.6 Other adverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal : The generation of waste should be avoided or minimized wherever

possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the

requirements of all authorities with jurisdiction.

Hazardous waste : The classification of the product may meet the criteria for a

hazardous waste.

Packaging

Methods of disposal : The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or

landfill should only be considered when recycling is not feasible.

Special precautions : This material and its container must be disposed of in a safe way.

Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

Regulatory		UN -	Hazard	Packing group	Additional
information	name	Number	classification		information
ADN	Not Restricted.			-	
ADR	Not Restricted.			-	
IATA	Not Restricted.			-	
IMDG	Not Restricted.			-	
DOT (U.S.A.)	Not Restricted.			-	
(Pictograms)					
Mexico Classification	Not Restricted.			-	
TDG Class	Not Restricted.			-	

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorization

Annex XIV: None of the components are listed.

Substances of very high concern:

Other EU regulations

Europe inventory

Integrated pollution prevention and control list (IPPC) - Air

Integrated pollution prevention and control list (IPPC) - Water

Not determined. Not determined.

Not listed

Not listed

Aerosol dispensers

Seveso II Directive

Not applicable.

This product is not controlled under the Seveso II Directive.

National regulations

References

: - Guide de la loi et du règlement sur le transport des marchandises dangeureuses au Canada. Centre de conformité international Ltée. 1986.

International regulations

Chemical Weapons Convention List Schedule I Chemicals

Chemical Weapons Convention List Schedule II Chemicals

Chemical Weapons Convention List Schedule III Chemicals : Not listed

: Not listed

: Not listed

15.2 Chemical Safety Assessment

: This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

Abbreviations and acronyms

: ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation

[Regulation (EC) No. 1272/2008] DNEL = Derived No Effect Level DMEL = Derived Minimal Effect Level

EUH statement = CLP-specific Hazard statement PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number

vPvB = Very Persistent and Very Bioaccumulative

Key literature references and sources for data

 Guide de la loi et du règlement sur le transport des marchandises dangeureuses au Canada. Centre de conformité international Ltée. 1986.

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Acute Tox. 4, H332 (inhalation)	Calculation method
Eye Dam./Irrit. 2, H319	Calculation method

Full text of abbreviated H statements

H302 (oral)	Harmful if swallowed.
H312 (dermal)	Harmful in contact with skin.
H332 (inhalation)	Harmful if inhaled.
H412	Harmful to aquatic life with long lasting effects.
H319	Causes serious eye irritation.
H226	Flammable liquid and vapor.
H315	Causes skin irritation.

Full text of classifications [CLP/GHS]

Acute Tox. 4, H302	ACUTE TOXICITY (oral) -
	Category 4
Acute Tox. 4, H312	ACUTE TOXICITY (dermal) -
	Category 4
Acute Tox. 4, H332	ACUTE TOXICITY (inhalation)
	- Category 4
Aquatic Chronic 3, H412	AQUATIC HAZARD (LONG-
	TERM) - Category 3
Eye Dam./Irrit. 2, H319	SERIOUS EYE DAMAGE/
	EYE IRRITATION - Category 2
Flam. Liq. 3, H226	FLAMMABLE LIQUIDS -
	Category 3
Skin Corr./Irrit. 2, H315	SKIN
	CORROSION/IRRITATION -
	Category 2

Date of printing: 04.02.2016Date of issue/ Date of revision: 07.10.2015Date of previous issue: 22.07.2015Version: 2.11

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.