

LAMINATED BACKLIT 610GSM

ITEM	METRIC		TEST METHOD
Weight	Gsm	610±10	DIN53352 BS3424
Breaking Strength	N/5cm	1100/1400	DIN53354 BS3424
Tearing Strength	N	130/180	DIN53356 BS3424
Adhesion	N/5cm	60	DIN53357 BS3424
Width	upto 510cm	(500x1000)	18x12
FR Certification	We can reach: M2, B1, B2, DIN75200, NFPA701		
Lacquering	Products can be lacquered with Acrylic		
Cd%, Pb%, As%, Ba%, Cr%, Hg%, Se%	EU.REACH Pre-Registered		
Conclusions & Announcements	Declaration by MATRIX: Please choose MATRIX products suitably according to relative provisions or industrial standards. MATRIX bears the responsibility for the specified technical and performance data on this page only. MATRIX is not responsible for any other liability. (The technical data on this page is calculated on average, and ±5% tolerance is acceptable) Remarks: 'G' represents Glossy surface, "M" represents Matte surface, Glossy or Matte could be made as requirements		

* Our product enables us to have vivid colors and good printing quality. (Test printing is suggested before the printing job.)



INK TYPE



SOLVENT



ECO-SOLVENT



UV



All above-released specifications and information are for guidance purposes only. Our policy of continuous improvement may result in changes. We therefore reserve the right to alter the specifications and the information at any time without notice.