

Technical Data Sheet

www.soletex.com

Article- No	KW 119 - MARS FR (Black Back)
Application	Display Roll Up System / Stage Decoration Backdrop / Frontlit / Roller Blind
Printable Ink	Treatment applied for Sub Paper , Direct Sub., Latex, Uv-Curable
Material	100 % Polyester
Standart Sizes	260, 320, 505 cm (102", 126", 199") * 50 mt (54 yrd.)
Weight	250 (g/m2)+ 5(gr) (8.8 oz)
Finishing	Digital Coating
Packaging	3" paper core, wrapped with stretch film + put in a cardboard box or tubes

Our product enables to have vivid colors and good printing quality with SUBLIMATION, UV & LATEX inks.

(Test printing is suggested before the printing job.)



Ink
Type

SUB

Sub Direct
and Paper
Transfer

UV

UV
Printable

LTX

Latex
Printable

*Optional



Fire
Ret.

B1

Fire
Retardant

M1

Fire
Retardant

**EN
13501**

Fire
Retardant

**NFPA
701**

Fire
Retardant



Cutting

COLD

Cold Cut

All above released specifications and informations are for guidance purposes only.
Our policy of continuous improvement may result in changes , we therefore reserve the
right to alter the specifications and the informations at anytime without notice.